

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) A user interface of a machine tool, the user interface comprising:

a display that is divided into at least a first display region and a second display region, wherein the first display region permanently displays a main menu that provides selection of different main modes of the user interface, wherein each main mode is associated with a main window that is opened in the second display region when a main mode is selected in the main menu, wherein at least one of the main windows comprises a permanently displayed submenu that provides selection of different submodes, with each submode being associated with a subwindow that is opened when an associated submode is selected, wherein one or more of the main windows and the subwindows include input fields; and

an input unit for selecting the individual modes and for processing the input fields provided in a window,

wherein the display permanently displays which one of the main modes is selected, and wherein if in an original main mode, a particular subwindow was opened and a user switched from the original main mode to another main mode, then if the user switches back to the original main mode, the particular subwindow is opened upon return into the original main mode.

2. (Previously presented) The user interface of claim 1, wherein the selected main mode is marked in the main menu.

3. (Currently amended) The user interface of claim 1, wherein at least one of the subwindows comprises a permanently displayed sub-submenu for selecting different sub-submodes of a selected submode and a sub-subwindow associated with each sub-submode such that a sub-subwindow is opened when ~~with~~ its associated sub-submode is selected.

4. (Previously presented) The user interface of claim 3, wherein at least one of the main windows, the subwindows, or the sub-subwindows comprises:

a navigation menu for selecting different navigation modes that each graphically represent a region of the machine tool, and

a navigation window associated with each navigation mode such that a navigation window is opened within the at least one main window, subwindow, or sub-subwindow when its associated navigation mode is selected.

5. (Currently amended) The user interface of claim 3, wherein if in an original main mode, a particular ~~subwindow~~, sub-subwindow[[,]] or navigation window was opened, and a user switched from the original main mode to another main mode, if the user switches back to the original main mode from the other main mode, the particular ~~subwindow~~, sub-subwindow[[,]] or navigation window is opened upon return into the original main mode.

6. (Previously presented) The user interface of claim 3, wherein at least one of the main windows, the subwindows, or the sub-subwindows comprises at least one activity button for processing input fields provided therein, in which each activity button is associated with an activity button window.

7. (Previously presented) The user interface of claim 6, wherein when an activity button window is opened, switching-over to a different main window, subwindow, or sub-subwindow of the same main mode is blocked.

8. (Previously presented) The user interface of claim 4, wherein a sequence of the individual submodes, sub-submodes, and navigation modes within one main mode is oriented on the workflow of the machine tool.

9. (Previously presented) The user interface of claim 3, characterized in that at least one of the submenus and the sub-submenus is designed as tab menu bar.

10. (Previously presented) The user interface of claim 1, wherein the display and the input unit are formed by a touch screen.

11. (Previously presented) The user interface of claim 1, wherein at least one of the main windows or the subwindows comprises:

a navigation menu for selecting different navigation modes that each graphically represent a region of the machine tool; and

a navigation window associated with each navigation mode such that a navigation window is opened within at least one main window or subwindow when its associated navigation mode is selected.

12. (Previously presented) The user interface of claim 1, wherein at least one of the main windows or the subwindows comprises at least one activity button for processing input fields provided therein, in which each activity button is associated with an activity button window.

13. (Previously presented) The user interface of claim 1, wherein the main menu is displayed as a menu bar.

14. (Currently amended) A method of interfacing with a user of a machine tool, the method comprising:

displaying a first display region in a display;
displaying a second display region in the display;
permanently displaying a main menu in the first display region, wherein the main menu provides a selection of different main modes of the user interface, wherein each main mode is associated with a main window;
opening a main window in the second display region when ~~[[it]]~~ its associated main mode is selected in the main menu;
permanently displaying a submenu in at least one of the main ~~menus~~ windows, wherein the submenu provides a selection of different submodes that are each associated with a subwindow;
opening a subwindow when its associated submode is selected;
displaying input fields in one or more of the main windows and the subwindows;
enabling selection of one or more of a main mode or a submode through an input unit;
processing the input fields at the input unit; ~~[[and]]~~
permanently displaying in the display which one of the main modes is selected;
opening a particular subwindow in an original main mode;
receiving a selection to switch from the original main mode to another main mode;
receiving a selection to switch from the other main mode back to the original main mode;
and
opening the particular subwindow upon return to the original main mode.

15. (Previously presented) The method of claim 14, further comprising marking the selected main mode in the main menu.

16. (Currently amended) The method of claim ~~[[1]]~~ 16, further comprising:
permanently displaying in at least one of the subwindows a sub-submenu that enables selection of different sub-submodes of a selected submode;
associating with each sub-submode a sub-subwindow; and

opening a sub-subwindow when its associated sub-submode is selected.

17. (Previously presented) The method of claim 16, further comprising:
presenting a navigation menu having different navigation modes in at least one of the main windows, the subwindows, or the sub-subwindows, wherein each navigation mode represents a region of the machine tool;
associating a navigation window with each navigation mode; and
opening a navigation window within the at least one main window, subwindow, or sub-subwindow when its associated navigation mode is selected.

18. (Currently amended) The method of claim 16, further comprising:
opening a particular ~~subwindow~~, sub-subwindow[[,]] or navigation window in an original main mode; and
receiving a selection to switch from the original main mode to another main mode;
receiving a selection to switch from the other main mode back to the original main mode;
and
opening the particular ~~subwindow~~, sub-subwindow[[,]] or navigation window upon return to the original main mode.

19. (Previously presented) The method of claim 16, further comprising:
presenting an activity button in at least one of the main windows, the subwindows, or the sub-subwindows, wherein an activity button supports processing of input fields provided in the at least one main window, subwindow, or sub-subwindow; and
associating each activity button with an activity button window.

20. (Previously presented) The method of claim 19, further comprising blocking switching to a different main window, subwindow, or sub-subwindow of a main mode when an activity button window is opened.

Applicant : Stephen Lausterer et al.
Serial No. : 10/550,078
Filed : June 7, 2006
Page : 7 of 14

Attorney's Docket No.: 15540-064US1 / 27143;
Trumpf: 18.00287; DS08100

21. (Previously presented) The method of claim 16, further comprising designing at least one of the submenus or sub-submenus as a tab menu bar.